

ELECTRODEIONIZATION STACK RALEX[®] MPure[™] 12

APPLICATION:

MPure[™] electrodeionization (EDI) stacks are used for the production of high purity water for the power generation, semiconductor, chemical and other industries.

DESCRIPTION:

EDI produces high purity water continuously without the use of hazardous regeneration chemicals required for the conventional mixed-bed process. The novel MPure[™] stacks are capable of producing up to 18 MΩ·cm quality at a high recovery.

MPure[™] stacks rely on MEGA's ion-exchange membrane manufacturing capability and extensive experience in the field of electromembrane separation processes. All stacks include RALEX[®] ion-exchange membranes developed by MemBrain.

FEATURES:

- Excellent demineralisation performance
- Robust design without internal and external leaks
- Small footprint
- Voltage stability
- Effective replacement for competing EDI technology

FEED WATER SPECIFICATIONS

Parameter	Value
Feed water source	RO permeate
Temperature [°C]	5 – 40
TEA [mg/L as CaCO ₃]	< 25
TEC [mg/L as CaCO ₃]	< 25
Oxidizers (chlorine or chloramine, ozone) [mg/L Cl ₂]	< 0.05
Heavy metals (Fe, Mn) [mg/L]	< 0.01
(Hydrogen)sulfides [mg/L]	< 0.01
Oils, greasy substances [mg/L]	#ND*
Detergents [mg/L]	#ND*
Suspended and colloidal matter [mg/L]	#ND*
Turbidity [NTU]	< 0.1
Silt density index SDI15	< 1
Microorganisms [cfu]	#ND*
Hardness [mg/L as CaCO ₃]	< 1
Organic substances [mg/L TOC]	< 0.5
Silica (dissolved) [mg/L SiO ₂]	< 1

*below the detection limit

RALEX® MPure™ 12 stack
Physical Specifications

Number of cell pairs	12
Dimensions (W×H×D) [mm]	584 x 811 x 335
Weight [kg]	157

Performance

Product flow min. – max. (nominal) [L/h]	1670 – 5000 (3330)
Concentrate flow [L/h]	100 – 667
Electrode flow [L/h]	100 – 200
Typical recovery [%]	80 – 96.2
Feed water pressure [bar]	< 5
Product pressure drop at nominal flow [bar]	1.1 – 2.5
Current [A]	< 16
Voltage [V DC]	< 100
Product water quality [$\mu\text{S}/\text{cm}$]	0.055 – 0.2*

*Actual performance depends on site conditions. Use the MPure™ Design projection software to predict the product quality and operating conditions.

Stack dimensions:
